

# INSTALLATION INSTRUCTIONS

## Product

**Dodge Caravan Base - 2008 and newer**  
7160-0116

Revision  
C

Form #  
INST-383



## WARNING



- You must read and follow all of these installation instructions. Failure to follow all of these installation instructions may result in serious bodily injury or death.
- The installer and user of the Dodge Caravan Base are responsible for installing and using Upper Pole, Motion Attachment and Dock or Cradle assemblies outside the airbag deployment zone. (See Product Mounting Disclaimer Below)
- Keep these installation instructions with the product and readily available in the vehicle for future reference of other users of the product.
- Additional copies of the installation instructions can be obtained from Gamber-Johnson. If you need assistance or have any questions, call Gamber-Johnson at 1-800-456-6868.
- Do not remove warning label from product under any circumstances.

Installation of the 7160-0116 Dodge Caravan Base will limit the forward travel of the front passenger seat.

On vehicles with Stow & Go Rear seating, this may cause the rear passenger seat to not stow properly or to not stow at all.



Move the front passenger seat rearward to gain access to the front inboard and outboard bolts. Remove the nuts from the bolts. Place an open ended wrench between the seatrail and seatbase onto the jam nut. Unscrew bolts using torx bit until you are able to lift seat enough to slide item 7160-0116 between the seatrail and seatbase. Retighten bolts back down and replace the nuts.

Remove front nuts.

### Product Mounting Disclaimer

Gamber-Johnson is not liable under any theory of contract or tort law for any loss, damage, personal injury, special, incidental or consequential damages for personal injury or other damage of any nature arising directly or indirectly as a result of the improper installation or use of its products in vehicle or any other application. In order to safely install and use Gamber-Johnson products full consideration of vehicle occupants, vehicle systems (i.e., the location of fuel lines, brakes lines, electrical, drive train or other systems), air-bags and other safety equipment is required. Gamber-Johnson specifically disclaims any responsibility for the improper use or installation of its products not consistent with the original vehicle manufactures specifications and recommendations, Gamber-Johnson product instruction sheets, or workmanship standards as endorsed through the Gamber-Johnson Certified Installer Program.

© copyright 2011 Gamber-Johnson, LLC

If you need assistance or have questions, call Gamber-Johnson at 1-800-456-6868



Jam Nut

After loosening bolts lift seat slightly and slide in 7160-0116.

Jam Nut



Completed assembly.

## WARNING

- The Upper Pole, Motion Attachment and Dock or Cradle should not be positioned in the area where the airbag will be deployed if it is activated. DO NOT position the equipment in front of an airbag. Equipment positioned in front of an airbag can cause serious injury or death if an airbag was activated, such as in an accident.
- If installation of the equipment requires that the equipment be placed in front of an airbag, deactivate the airbag in the vehicle so it cannot be activated in an accident. In order to secure permission for deactivating the airbag in these circumstances, contact the National Highway Traffic Safety Administration at 1-800-424-9393 to gain permission to do so. If you have any questions or need assistance, call Gamber-Johnson at 1-800-456-6868.
- High speed vehicle turns may cause a Motion Attachment product to swivel, interfering with the driver or other equipment.